

## HS-SODIMM-S1



### Introduction

Hikvision memory module S1 is a DDR3 memory, which is manufactured by using original high-quality granules and mature production technology to make it more compatible, work stable and cost-effective. It can be widely used in notebook computer installation.

### Available Models

| Capacity | Model                          |
|----------|--------------------------------|
| 4GB      | HS-SODIMM 4G HKED3042BAA2A0ZA1 |
| 4GB      | HS-SODIMM 4G HKED3042AAA2A0ZA1 |
| 8GB      | HS-SODIMM 8G HKED3082BAA2A0ZA1 |

\*Please contact your local sales representative for detailed ordering information

### Features and Functions

- Cost-effective

Adopt original granules to make the system run stably and perform better

- Good compatibility

Better compatibility, compatible with more products after Hikvision optimization

## Specifications

|                         |                                   |                                   |                                   |
|-------------------------|-----------------------------------|-----------------------------------|-----------------------------------|
| Name                    | HS-SODIMM-S1                      |                                   |                                   |
| Model                   | HS-SODIMM 4G<br>HKED3042BAA2A0ZA1 | HS-SODIMM 4G<br>HKED3042AAA2A0ZA1 | HS-SODIMM 8G<br>HKED3082BAA2A0ZA1 |
| Capacity                | 4GB                               | 4GB                               | 8GB                               |
| Interface               | DDR3                              |                                   |                                   |
| frequency               | 1600MHz                           |                                   |                                   |
| Pin                     | 204pin                            |                                   |                                   |
| CAS Latency             | CL11                              |                                   |                                   |
| Working Voltage         | 1.35V                             |                                   |                                   |
| Size(L×W×H mm)          | 67.6×30.0×1.0                     |                                   |                                   |
| Operation temperature   | 0 °C to 85 °C (32 °F to 185 °F)   |                                   |                                   |
| Limited warranty period | Lifetime warranty                 |                                   |                                   |

## Update

| Version number | Time     | Updater    |
|----------------|----------|------------|
| V1.0           | 20200901 | Fanxin Xue |

The data is subject to change without notice.

Copyright © Hangzhou Haikang Storage Technology Co., Ltd. 2020. All rights reserved.

Unless otherwise agreed, the company does not provide any express or implied statement or guarantee for this manual.

This manual is only used as a guide for related products and may differ from the actual product. Please refer to the actual product. Due to product version upgrades or other needs, this

The company may update this manual. If you need the latest version of the manual, please consult the sales staff in your area or log on to the company's official website.

([www.hikstorage.com](http://www.hikstorage.com))